

# ASA | 一般特性

透明 ABS					一般 ASA		挤出 ASA			耐热 ASA
透明性					一般注塑性		挤出性			耐热性
TR551	TR552	TR556	TR557	TR558A	LI911	LI912	LI913	LI968W	LI970	LI941
580	390	420	450	500	500	480	410	480	460	480
57	38	41	44	49	49	47	40	47	45	47
8,200	5,500	6,000	6,400	7,100	7,100	6,800	5,800	6,800	6,500	6,800
28,000	18,000	21,200	21,400	22,200	22,100	21,200	17,600	20,400	20,200	20,400
2,750	1,770	2,080	2,100	2,180	2,170	2,080	1,730	2,000	1,980	2,000
398,000	256,000	301,000	304,000	315,000	314,000	301,000	250,000	290,000	287,000	290,000
6	8	8	5	6	6	6	5	6	6	6
40	51	50	40	40	20	25	35	25	23	25
960	600	680	680	780	800	780	660	790	760	770
94	59	67	67	76	78	76	65	78	75	76
13,600	8,500	9,700	9,700	11,100	11,300	11,000	9,380	11,000	10,900	11,000
28,000	17,700	19,200	21,000	25,000	23,500	22,500	19,500	24,000	24,000	23,500
2,740	1,730	1,880	2,060	2,450	2,300	2,200	1,910	2,350	2,350	2,300
398,000	251,000	273,000	298,000	355,000	334,000	320,000	277,000	341,000	341,000	334,000
11	25	16	15	11	12	16	35	14	13	14
108	250	160	150	108	120	160	340	140	130	140
2.0	4.6	2.9	2.8	2.0	2.2	2.9	6.0	2.6	2.4	2.6
6	10	7	7	5	3	4	6	4	4	4
59	98	69	69	49	30	40	59	40	40	40
1.1	1.8	1.3	1.3	0.9	0.6	0.7	1.1	0.7	0.7	0.7
12	27	17	16	11	14	18	45	18	16	17
120	260	170	160	108	140	180	440	180	160	170
2.2	5.0	3.1	2.9	2.0	2.6	3.3	8.0	3.3	2.9	3.1
6	10	7	7	5	-	-	-	-	-	-
59	98	69	69	49	-	-	-	-	-	-
1.1	1.8	1.3	1.3	0.9	-	-	-	-	-	-
118	97	105	108	113	107	103	93	103	100	105
91	82	88	86	87	96	97	97	97	93	105
196	180	190	187	189	205	207	207	207	200	221
87	79	83	82	83	87	87	86	87	82	97
189	174	181	180	181	188	189	186	189	180	207
99	92	96	96	97	101	101	102	101	98	107
210	198	205	205	207	215	215	216	215	208	225
94	87	92	90	92	96	96	96	96	92	104
201	189	198	194	198	205	204	205	204	198	219
90	84	92	85	88	96	95	94	95	93	104
194	183	198	185	190	204	203	200	203	200	219
HB	HB	HB	HB	HB	HB	HB	HB	HB	HB	HB
-	-	-	-	-	-	-	-	-	-	-
HB	HB	HB	HB	HB	HB	HB	HB	HB	HB	HB
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
1.13	1.06	1.09	1.09	1.11	1.07	1.07	1.07	1.07	1.07	1.07
0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7
1.00	1.00	1.00	2.00	2.00	2.00	1.20	0.50	1.30	1.20	0.50
9.00	12.00	5.00	24.00	26.00	20.00	12.00	6.00	13.00	12.00	6.00
4.00	5.00	2.00	8.00	10.00	7.00	3.00	2.00	4.00	3.00	2.00
High Rigidity	Chemical Resistance	Exclusion	High Impact	Standard	高流动 注塑	标准 注塑	高抗冲 挤出	耐候性 共挤出	耐Scratch性 共挤出	耐热 耐热

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 [www.kedisujiao.com](http://www.kedisujiao.com)

备注：以上原料物性数据由厂家发布，我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！